

TASETO 不锈钢用 TIG 填充丝

牌号	识别颜色		对应的型号		化 学			
			JIS	AWS	C	Si	Mn	P
TG308H	黄	—	YS308H	ER308H	0.04~ 0.08	≤0.65	1.0~ 2.5	≤0.03
TG310S	桃	—	YS310S	—	≤0.08	≤0.65	1.0~ 2.5	≤0.03
TG317L	栗色	—	YS317L	ER317L	≤0.03	≤0.65	1.0~ 2.5	≤0.03
TG347L*	青	红	YS347L	ER347	≤0.03	≤0.65	1.0~ 2.5	≤0.03
TG347HT	青	青	YS3347	ER347	0.04~ 0.08	≤0.65	1.0~ 2.5	≤0.03
TG329J3L	红	绿	YS2209	ER2209	≤0.03	≤0.90	0.5~ 2.0	≤0.03
TG329J4L	红	青	YS329J4L	ER2594	≤0.03	≤0.90	0.5~ 2.5	≤0.03

成分(%)							用途
S	Ni	Cr	Mo	Nb	Cu	N	
≤0.03	9.0~11.0	19.5~22.0	≤0.50	—	≤0.75		SUS304 用
≤0.03	20.0~22.5	25.0~28.0	≤0.75	—	≤0.75	—	SUS310S 用
≤0.03	13.0~15.0	18.5~20.5	3.0~4.0	—	≤0.75	—	SUS317,317L 用
≤0.03	9.0~11.0	19.0~21.5	≤0.75	10×C% ~1.0	≤0.75	—	SUS347,321 用
≤0.03	9.0~11.0	19.0~21.5	≤0.75	10×C% ~1.0	≤0.75	—	SUS347,321 用
≤0.03	7.5~9.5	21.5~23.5	2.5~3.5	—	≤0.75	0.08~0.20	SUS329J3L 用
≤0.03	8.0~11.0	23.0~27.0	3.0~4.5	—	≤1.0	0.08~0.30	SUS329J4L 用